

Greaves 'D' Series Diesel Generating Sets

Genset Model with the Canopy	KVA @ 50 Hz	KW @ 0.8 PF	Model	BHP at 1500 rpm	Cooling	Dimensions Of DG Set/Canopy in mm (approx.)*			Weight Kgs.**approx Nett. For genset	Weight in Kgs.** approx with 5 sides canopy
						Length	Width	Height		
GW-125 SP	125	100	TD4L4K	156	Radiator	2400/3500	775/1500	1400/1735	1350	2810*
GW-140	140	112	TBD2 V6K	169	Radiator	2500/3500	990/1500	1670/1900	1980	3440 *
GW-180	180	144	TBD3 V6K	230	Radiator	2500/3500	990/1500	1670/1900	2175	3135 *
GW-200	200	160	TBD3V6 MK 1K	253	Radiator	2500/3500	1145/1500	1670/1900	2250	3810 *
GW-250	250	200	TBD3 V8K	313	Radiator	2775/4000	1270/1600	2127/2000	2525	NA
GW-275	275	220	TBD2 V12K	342	Radiator	2300/5200	1000/2000	1615/2300	2700	NA
GW-520	520	400	TBD4 V12K	604	Radiator	3985/5300	1320/2000	2260/2400	4600	7075
GW-520 SP	520	416	TBD4I V12K	604	Radiator	3985/5300	1320/2000	2260/2400	4600	7075

* Dimensions are given for close coupled D.G.sets

** In view of continuous improvement the specifications are subject to change without notice.

In view of continuous improvement the specifications are subject to change without notice.

- Lists includes standard fast moving models only.
- Rating as per BS:5514, ISO:3046, IS:10000
- 10 % Overload permitted for 1 hour in each 12 hours.
- Power outputs at 1500 rpm, 50 Hz
- Heat exchanger cooled versions are also available. (Refer separate catalogue for details.)
- * - Dry weight for five sided canopy with Control panel & Fuel tank.
- DG sets also available with Synchronising panel for parallel running operations.
- DG sets with Auto Mains failure systems (AMF) available.
- DG sets with sound proof enclosures available.
- Dual fuel DG sets available.
- Special ratings can be offered on request, for defence, marine & other applications for bulk supplies.
- All dimensions are subject to exchange without notice.